

# PXie SERIES PRINTERS

## High-Performance Industrial Printers

The PXie Series industrial printers are built to meet the needs of round-the-clock, mission-critical applications. These rugged printers deliver advanced connectivity and network protocols, ensuring peace of mind today and a reliable, scalable solution for the long haul.



*The PXie Series industrial printers are flexible, compact, and programmable, enabling customers to optimize their printing operations, streamline deployment, and achieve quick return on investment.*

The rugged, all-metal PXie printers deliver outstanding performance – up to 12 inches per second from first label to last – and incorporate features that reduce downtime and minimize maintenance costs. Both versions are available with 203 or 300 dpi resolution, and the PX4ie also offers 406 dpi, for precision labeling without any loss of speed. This is ideal for compliance labeling applications with variable data requiring immediate results.

The PXie printers' smart design features support increased productivity in demanding environments. As Smart Printers, they can host stand-alone applications, developed through the Fingerprint and C# programming languages, helping reduce errors and streamline operational processes.

The printers' device management and diagnostic capabilities – provided in web-based PrintSet Configuration Management, and soon to be released in AirWatch®, SOTI™, and Operational Intelligence – reduce downtime and simplify deployment.

Replacing printheads is fast and easy, thanks to the magnetic QuickMount™ printhead design. The PXie printers are co-engineered and tested with Honeywell labels and other media products, optimizing performance when used with genuine Honeywell media.

## FEATURES AND BENEFITS



The PXie printers' compact, modular design facilitates integration into automated labeling applications.



Smart Printers can eliminate the PC and control other devices directly (such as scanners, scales, and applicators), improving efficiency and decreasing infrastructure costs and complexity.



With user-selectable, all-in-one printer command languages (DP/FP, IPL, ZSim, DPL), the PXie printers fit with drop-in simplicity in mixed printer environments, supporting fast deployment.



Every printer ships with Ethernet connectivity and network protocol IPv6, ensuring long-term, enterprise scalability. Multiple interface options are available, including the highest level of secure wireless connectivity (WPA2).



**Honeywell Partner**  
Beratung-Verkauf-Service  
Integer Solutions GmbH  
Industriestraße 4, 61200 Wölfersheim  
Tel.: +49-6036-90557-0  
[www.integer-solutions.com](http://www.integer-solutions.com)

**Honeywell**

# PXie SERIES INDUSTRIAL PRINTERS Technical Specifications

## PHYSICAL DESCRIPTION

Direct thermal and thermal transfer label, ticket, and tag printer. Also available with RFID.

## PHYSICAL CHARACTERISTICS

### L x H x W:

**PX4ie:** 482 mm x 238 mm x 275 mm  
(19.0 in x 9.4 in x 10.8 in)

**PX6ie:** 482 mm x 238 mm x 335 mm  
(19.0 in x 9.4 in x 13.2 in)

### Weight:

**PX4ie:** 12.61 kg (27.87 lbs)

**PX6ie:** 14.13 kg (31.12 lbs)

## PRINT SPECIFICATIONS

### Max. Print Width:

**PX4ie:** 112 (DT)/110 (TT) mm  
(4.4/4.3 in)

**PX6ie:** 167.4 mm (6.59 in)

### Max. Length:

**At 203 dpi:** 4095 mm (161 in)

**At 300 dpi:** 2775 mm (109 in)

**At 406 dpi:** 1016 mm (40 in)

## RFID STANDARDS & FREQUENCIES

Supports 18000-6C / EPC Generation 2 865-928 MHz radio configured to comply with local UHF RFID regulations including FCC and ETSI. Contact local representative for availability in particular region.

## PRINT SPEED

### PX4ie:

**For 203/300 dpi:** 100–300 mm/s  
(4–12 ips)

**For 406 dpi:** 100–250 mm/s  
(4–10 ips)

### PX6ie:

**For 203/300 dpi:** 100–225 mm/s  
(4–9 ips)

### Resolution:

**PX4ie:** 8 dots/mm (203 dpi), 11.8 dots/mm (300 dpi), 16 dots/mm (406 dpi)

**PX6ie:** 8 dots/mm (203 dpi), 11.8 dots/mm (300 dpi)

## MEDIA

**Type:** Labels and Tags

### Max/Min Width:

**PX4ie:** 120/25.4 mm (4.72/1 in)

**PX6ie:** 170/76 mm (6.70/3 in)

**Thickness:** 2.4 to 10.0 mil

**Configuration:** Roll-fed or fanfold

**Sensing:** Gap, notch, black mark, continuous

**Label Roll Max Diameter:** 213 mm (8.38 in)

**Label Roll Core:** 38–76 mm (1.5–3 in)

**Type:** Ribbons

**Roll Max Diameter:** 80 mm (3.15 in), approx. 450 m

**Core ID:** 25.4 mm (1 in)

**Type:** Wax, mid-range, resin

## INTERFACES

### Standard:

**Ethernet:** 10/100 Mbps

**RS-232:** up to 115.2 KB/s

### Supported Serial Protocols:

**Fingerprint/Direct Protocol:** XON/XOFF, ENQ/ACK, DTR, RTS/CTS

**IPL:** XON/XOFF, Honeywell Std. Protocol

**USB:** 2.0

### Optional:

**Parallel:** IEEE 1284

**Industrial Interface:** 8 digital in/out, 4 analog relays, 1 RS-232/422/485 port

**Dual Serial Ports:** RS-232, RS-422, RS-485, and 20 mA Current Loop

### Applicator Interface

### Wireless:

IEEE 802.11 a/b/g/n/ac

Wi-Fi Certified

WEP, WPA, WPA2, 802.11x (EAPTTLS, LEAP, PEAP, FAST)

Multiple industrial antenna options for maximized coverage

**Supported Protocols:** TCP/IP-suite (TCP, UDP, ICMP, IGMP, etc.), LPR/LPD, FTP, BOOTP, DHCP, HTTP, SNMPv3, SMTP. SNMP-MIB II supported (over UDP/IP), private enterprise MIB included. Supports IPv4 and IPv6, NTP

## SOFTWARE

**Printer Command Languages:** Fingerprint (FP), Direct Protocol (DP), IPL, ZSim2 (ZPL-II), DPL; XML enabled for SAP® All and Oracle® WMS

**Applications/Drivers:** InterDriver Windows® printer driver, CUPS driver for Linux, Honeywell Device Types for SAP, Honeywell label design and print package

### Smart Printing Languages:

**Honeywell C# for Printers:** Smart Printing Developer Resource Kit; write apps with .NET-compatible development environments

**Configuration and Device Management Support:** PrintSet for printer configuration; sophisticated web interface for configuration, upgrades, and 1:1 management

**Device Management Support (to be included in future release):** AirWatch, SOTI, Operational Intelligence

## BARCODE SYMBOLOGIES

All major 1D and 2D symbologies are supported.

## STANDARDS SUPPORTED

UPC/EAN Shipping Container

UCC/EAN 128 Serial Shipping Container

MH10.8 Shipping Label

AIAG (shipping parts label)

OGMARS

POSTNET

HIBCC

ISBT 128

GM1724

UPS shipping label

Global Transport label



**Honeywell Partner**  
Beratung-Verkauf-Service  
Integer Solutions GmbH  
Industriestraße 4, 61200 Wölfersheim  
Tel.: +49-6036-90557-0  
www.integer-solutions.com

# PXie SERIES INDUSTRIAL PRINTERS Technical Specifications

## FONTS

Monotype font engine; non-Latin fonts available through WTLE

## GRAPHICS

Supports PCX, PNG, GIF, and BMP file formats. Other formats supported with Label Generation Tools.

## MEMORY

**Standard:** 128 MB Flash memory, 256 MB DDR2 SDRAM

**Available:** Multi-GB USB memory device (FAT16/FAT32 USB drivers supported)

**Built-in RTC**

## KEYPAD CONTROL PANEL

Interactive numeric keypad control panel  
2.3 in color LCD

## POWER SUPPLY

**AC Voltage:** 90 to 265V AC, 45 to 65 Hz

**PFC Regulation:** IEC 61000-3-2

**Power Consumption:**

Standby 5W

Continuous average 125W

Peak 400W



**For more information**

[www.honeywellaidc.com](http://www.honeywellaidc.com)

## OPERATING ENVIRONMENT

**Ambient Operating Temperature:** +5°C to +40°C (+41°F to +104°F)

**Storage Temperature:** -20°C to +70°C (-4°F to +152°F)

**Humidity:** 10% to 90% non-condensing

## REGULATORY APPROVALS

CE (EN55022 Class B), FCC Class B, UL/cUL, C-Tick

Energy Star 3.0 (excludes non Wi-Fi parallel port SKUs)

## OPTIONS

RFID, integral self-strip unit with liner take-up, Label Taken Sensor (LTS), alphanumeric keyboard\*, parallel interface board, additional serial interface board\*, industrial interface board\*, applicator interface board\*\*, media supply hub, cutter, label low sensor

\*Not applicable when using IPL firmware.

\*\* Supported for Direct Protocol and Fingerprint printer languages.

For a complete listing of all compliance approvals and certifications, please visit [www.honeywellaidc.com/compliance](http://www.honeywellaidc.com/compliance).

For a complete listing of all supported barcode symbologies, please visit [www.honeywellaidc.com/symbologies](http://www.honeywellaidc.com/symbologies).

AirWatch is a trademark or registered trademark of VMware, Inc.

Oracle is a trademark or registered trademark of Oracle Corporation.

SAP is a trademark or registered trademark of SAP SE.

SOTI is a trademark or registered trademark of SOTI Inc.

Windows is a trademark or registered trademark of Microsoft Corporation.

All other trademarks are the property of their respective owners.



**Honeywell Partner**  
Beratung-Verkauf-Service  
Integer Solutions GmbH  
Industriestraße 4, 61200 Wölfersheim  
Tel.: +49-6036-90557-0  
[www.integer-solutions.com](http://www.integer-solutions.com)